

High Spin Dryers for Excellent Performance on Thin Film.

Mechanical drying is required to dewater washed plastics. An efficient drying can only be achieved through the application of tremendous force. Most dryers available on the machinery market operate at a low rotor speed, resulting in poor drying performance. To manage the high spin rate, precisely balanced rotors are required. The design of these rotors is crucial.



High Spin Acceleration, Massive Airflow and Screen Auto-Clean

Pla.to offers a unique jacket rotor design which allows high spin rotation. The acceleration of the rotor plates spin the plastic at a maximum speed. Clumps of film are quickly loosened into single flakes.

An integrated blower sucks the material into the machine and forces it out of the machine. This process prevents jams and increases the performance.

The dryer is able to spin off residual contamination that was not removed during upstream processing, such as residual fibres from decomposed paper.

A continuously rotating scraper automatically cleans the screen and housing of the dryer.

This cleaning feature is essential to move any contamination out of the machine.

Polygonal screen baskets increase the drying and cleaning efficiency of the machine. The screens and screen holders are made of stainless steel to ensure a rust-free product.



	SD90-90	SD132-130	SD200-140	SD250-180	SD250-200
Performance rigid Flake [kg/h]	2000 – 2500	4000 – 5000	5000 – 6000	6000 – 8000	8000 – 10000
Performance Film [kg/h]	500 – 700	700 – 1200	1200 – 1800	2000 – 2500	2500 – 3000
Main Motor [kW]	90	132	200	200 – 250	250
Basket Diameter approx. [mm]	900	1300	1400	1800	2000
Scraper Drive [kW]	0.55	0.75	0.75	0.75	0.75

The achievable throughput capacity depends on the particle size and material thickness.



Pla.to GmbH
Nickrischer Strasse 20
02827 Goerlitz
Germany

Phone +49 35822 312735
E-Mail info@plato-technology.de
Web www.plato-technology.de